



Intellical CDC401 Laboratory 4-Poles Graphite Conductivity Cell, 1 m Cable

Product #: CDC40101

ZAR Price: Contact Hach

Available

Intellical CDC401 is a digital, graphite, 4-pole conductivity cell with a temperature sensor. The laboratory version is available with a 3 or 1 m cable. The CDC401 is ideal for measuring electrical conductivity, salinity, resistivity, or total dissolved solids (TDS) in wastewater, drinking water, or general water quality applications.

Intellical digital probes provide ultimate traceability in conductivity measurement history

Stored time and date stamp for each measurement, operator and sample ID, calibration history, parameter, and probe serial number.

Intellical CDC401 digital conductivity probes alert the user when re-calibration is needed

No guesswork needed to provide the most reliable and accurate results with each measurement.

Intellical CDC401 digital conductivity probes can be moved between meters without the need to re-calibrate or re-enter measurement settings

Ideal for a multi-user environment with multiple HQD series Laboratory and Portable meters.

Specifications

Accuracy:

Cable Length:	1 m
Electrode Type:	Standard
Kit?:	No
Length:	184 mm

Method Type: Laboratory: 4 Poles - Graphite

Parameter: Conductivity
Product Kit: Model: CDC401

Accessories Included: None

TDS: ±0.5% ±1 digit

Range: Conductivity: $0.0 \mu \text{S/cm} - 200 \text{ mS/cm}$

TDS: 0.00 mg/L - 50.0 g/L as NaCl

Salinity: 0 - 42 ppt or ‰

Resistivity: $2.5 \Omega cm - 49 M\Omega cm$

Resolution: 0.01/0.1 (5 digits max.)

Sensor material: Noryl

Sensor Type : 4-poles conductivity probe, Graphite, $k = 0.40 \text{ cm}^{-1}$

Temperature Accuracy: ±0.3 °C

Temperature Range: -10 - 110 °C

Temperature resolution: 0.1 °C

Test requirements: Parameter Needed: Conductivity

Minimum Sample Depth (mm): 45

Thermistor: ATC

Warranty: 12 months

Weight: 0.1 kg

What's included?: Intellical CDC401 Laboratory Conductivity Cell, 1 m cable, Test certificate, and Basic User

Manual.

What's included?

Intellical CDC401 Laboratory Conductivity Cell, 1 m cable, Test certificate, and Basic User Manual.