



HQ430D Water Quality Laboratory Biochemical Oxygen Demand (BOD) Meter Package with Optical LBOD101 Sensor

Product #:

25638018

ZAR Price:

Contact Hach

Ships within 1 week

The Hach HQ430D Multi-Meter is an advanced BOD meter designed for water quality experts to take the guesswork out of measurements. HQD meters connect with smart Intellical electrodes that automatically recognize the testing parameter, calibration history, and method settings to minimize errors and setup time. The advanced HQD Laboratory Meter is designed to withstand years of continuous lab use. HQD meters feature a simple user interface that does not require manuals or training to operate. The Intellical LBOD101 is the latest embodiment of Hach's patented Luminescent Dissolved Oxygen (LDO) technology. The LBOD101 is a digital, luminescent dissolved oxygen (LDO) sensor with a replaceable, integrated stirring system. The LBOD101 measures the dissolved oxygen for BOD (Biochemical Oxygen Demand) determination in BOD bottles in BOD5 testing applications. The LBOD101 electrode is used for initial and final dissolved oxygen measurements.

Make your Biochemical Oxygen Demand (BOD) water laboratory quality parameters testing more efficient and flexible

Single input channel for flexible measurement of pH, Conductivity, Total Dissolved Solid (TDS), Optical Dissolved Oxygen (DO), Biochemical Oxygen Demand (BOD), Oxydo Reduction Potential (ORP/RedOx), Temperature, Ion Selective Electrode (ISE) direct concentration reading for Ammonia, Ammonium, Fluoride, Chloride, Sodium - connect any Intellical™ smart probe.

Intuitive user interface for simple operation, reliable and accurate results

Guided calibration and check standard routines reduce calibration errors while stabilization alerts and visual measurement lock ensure that you can trust the accuracy of the results.

Trust your measurements - Intellical™ smart probes store all calibrations in the probe

Calibration history allows quick and easy change out of probes without re-calibrating. The HQD smart system records serial numbers, current calibration data, user ID, sample ID, time, and date automatically in the data log for complete Good Laboratory Practice (GLP) traceability.

Enhance data connectivity with easy to read results

Internal USB ports simplify data transfer, peripherals, and software updates and connection to PCs printer and keyboards, with a large ultra-bright backlit LCD screen with large font size for convenient reading.

Complete convenient kit

Package content includes everything you need to start testing. Details below

Specifications

Automatic Buffer Recognition:	Yes
Barometric Pressure Measurement:	Automatic compensation of DO when using an LDO or LBOD probe
BOD Bottle:	300 mL/100 pcs
BOD5/CBOD resolution:	Available when used with Hach WIMS BOD Manager software
Calibration Intervals/Alerts/Reminder:	Off, selectable from 2 hours to 7 days
CDC Electrode Calibration:	Demal (1D/ 0.1D/ 0.01D); Molar (0.1M/ 0.01M/0.001M);

	NaCl (0.05%; 25µS/cm; 1000µS/cm; 18mS/cm);
	Standard sea water;
	User defined
Communication:	Integrated USB type A (for USB 2.0 flash memory device, printer, keyboard) and Integrated USB type B (for PC)
Compliance Certifications:	CE.WEEE
Conductivity Measurement at Stable Reading:	Yes
Conductivity measurement: Temperature correction:	None; Linear; NaCl Non-Linear Natural Water.
Conductivity Range:	0.01 µS/cm - 200.0 mS/cm
Conductivity resolution:	0.01 µS/cm - 0.1 mS/cm upon selected measuring range
Contents:	Meter + Probe(s) + Lab. Accessories
Custom Calibration Standards:	Yes
Data Export:	Download via USB connection to PC or flash memory device. Automatically transfer entire data log or as readings are taken.
Data Memory:	500 records/FIFO
Data storage:	Automatic, GLP ISO compliant reading data stored with calibration details.
Dimensions:	859 x 175 x 235 mm
Display:	Detailed mode/Large mode
Display Type:	440 x 160 pixel LCD with backlight illumination
DO Measurement Range:	0.1 - 20.0 mg/L (ppm) 1 - 200% saturation
DO Resolution:	0.1
DO sensor calibration:	<ul style="list-style-type: none"> • 100% (water-saturated air (100%) calibration • 100% with 0 (water-saturated air (100%) calibration with 0 point • mg/L (calibration with a specified dissolved oxygen concentration (mg/L) solution) • mg/L with 0 (calibration with a specified dissolved oxygen concentration (mg/L) solution with 0 point) • Factory (calibration with the default LDO calibration)
Electrode Holder:	NA
Electrode stand:	Optional
Environmental Conditions: Relative Humidity:	90 % relative humidity (non-condensing)
Environmental Conditions: Temperature:	0 - +60 °C (32 - 140 °F)
GLP Features:	Date; Time; Sample ID; Operator ID
Instrument:	Bench
IP Rating:	IP54 (Resistant to spray of water; Dust-proof)
ISE Direct Measurement Range:	Yes
ISE Electrode Calibration:	2 - 5 points
Kit?:	Yes
Languages user interface:	English, French, German, Italian, Spanish, Danish, Dutch, Polish, Portuguese, Turkish, Swedish, Czech, Russian
Lock Function:	Continuous / Auto-stabilization ("press to read") / At Interval
Measurement method:	Luminescent Dissolved Oxygen
Model:	HQ430D – Multi/1 Channel

mV Measurement at Stable Reading:	Yes
mV Measurement Range:	-1500 - 1500 mV
mV Resolution:	0.1 mV
Needed Cable Length:	1
Operating Error Messages:	Clear text error messages displayed
Operating Interface:	Soft Touch Keypad
ORP Electrode Calibration:	Predefined ORP standards (including Zobell's solution)
Parameter:	pH/Oxydo Reduction Potential (ORP)
	Conductivity/Total Dissolved Solid (TDS)/Salinity/Resistivity
	Dissolved Oxygen (DO)
	Biochemical Oxygen Demand (BOD)
PC Data Transfer Software :	Ion Selective Electrode (ISE): Ammonia, Ammonium, Chloride, Fluoride, Nitrate, Sodium
	HQD Series Meter Data Transfer Utility
	pH Buffer Sets:
	Color-coded: 4.01, 7.00, 10.01 pH;
pH Electrode calibration:	IUPAC: 1.679, 4.005, 7.000, 10.012, 12.45 pH
	DIN: 1.09, 4.65, 9.23 pH
	User-defined custom buffer sets
	1 - 3 Calibration points
pH Measurement Range:	Calibration summary data logged and displayed
	0 - 14 pH
	pH Resolution:
	Selectable:
Printer:	0.001/0.01/0.1 pH
	Yes, Optional
	Probes included:
	LBOD10101
Range:	0.05 - 20.00 mg/L
Resistivity Measurement:	2.5 Ω.cm - 49 MΩ.cm
Resistivity Resolution:	0.1
Salinity Measurement Range:	0 - 42 (ppt) (‰)
Salinity Resolution:	0.01 (ppt) (‰)
Sensor A:	LBOD10101
Sensor B:	NA
Sensor C:	NA
Sensors:	Sensor A: LBOD10101
	Sensor B: NA
	Sensor C: NA
TDS Measurement Range:	0.00 mg/L - 50.0 g/L as NaCl
TDS Resolution:	0.01 mg/L - 0.1 g/L upon measuring range.
Temperature Compensation:	Automatic Temperature compensation for pH
Temperature Measurement:	°C or °F
Temperature Range:	-10°C - 110 °C

Temperature resolution:	0.1
Type of measurement:	Lab Wasterwater Monitoring
Warranty:	36 months
Weight:	750 g (1.65 lb) without batterie; 850 g (1.87 lb) with batteries
What's included?:	Meter package includes HQ430D Laboratory Multi Meter, LBOD101 Luminescent/Optical Dissolved Oxygen (LDO) electrode for BOD Measurement with 1 m cable, Disposable 300 mL BOD Bottle (100 pcs), BOD Bottle Stoppers (25 pcs), BOD Bottle cap (6 pcs), 4 Alkaline 1,5V AA batteries, Power Supply Adapter, Power Cord, USB cable for data transfer, and Operating Documentation.

What's included?

Meter package includes HQ430D Laboratory Multi Meter, LBOD101 Luminescent/Optical Dissolved Oxygen (LDO) electrode for BOD Measurement with 1 m cable, Disposable 300 mL BOD Bottle (100 pcs), BOD Bottle Stoppers (25 pcs), BOD Bottle cap (6 pcs), 4 Alkaline 1,5V AA batteries, Power Supply Adapter, Power Cord, USB cable for data transfer, and Operating Documentation.