



## HQ40D Portable Meter Package with PHC301 pH Electrode and CDC401 Conductivity Cell

Product #:

8507540

 **Hazardous**

**OBSELETE ITEM**  
This item is no longer available.

Items with this mark may be considered hazardous under some shipping conditions.

If necessary, we will change your selected shipping method to accomodate these items.

### Rugged portable meters for use in the field and plant.

Designed for your water applications, the Hach HQ40D portable meter is an advanced meter that takes the guesswork out of measurements. HQD meters connect with Intellical probes that automatically recognize the testing parameter, calibration history, and method settings to minimize errors and setup time.

Replaced by NEW HQ Series.

#### Portable meter measures critical water quality parameters - without the need for multiple instruments

Two input channels for simultaneous measurement of pH, Conductivity, TDS, Salinity, Dissolved Oxygen, BOD, ORP, Ammonia, Ammonium, Fluoride, Chloride, Sodium, and temperature - any Intellical smart probe.

#### Intuitive user interface for simple operation and accurate results

Guided calibration and check standard routines reduce calibration errors. Stabilization alerts and visual measurement lock ensure that you can trust the accuracy of the results.

#### Trust your measurements - Intellical smart probes store all calibrations in the probe

Calibration history allows quick and easy change out of probes without re-calibrating. The HQD smart system records serial numbers, current calibration data, user ID, sample ID, time, and date automatically in the data log for complete GLP traceability.

#### Designed for demanding conditions

Rugged, waterproof (IP67) meter provides worry-free, reliable operation in lab or field environments.

#### Convenient kit includes everything you need to start testing

Meter package includes HQ40D Portable Meter, gel PHC201 pH probe with 1 m cable, CDC401 conductivity/TDS/salinity probe with 1 m cable, pH buffer solutions, pH storage solution, NaCl conductivity standard, probe stand, meter stand, 4 AA batteries, protective meter glove, power adapter, USB/DC power adapter for data transfer, quick-start guide, user manual, and documentation

---

### Specifications

AC Power Adapter and USB/DC Adapter:	Included
Automatic Buffer Recognition:	Yes
Barometric Pressure Measurement:	Automatic compensation of DO when using an LDO or LBOD probe
Calibration Intervals/Alerts/Reminder:	Off, selectable from 2 hours to 7 days
CDC Electrode Calibration:	Demal (1D/ 0.1D/ 0.01D);  Molar (0.1M/ 0.01M/0.001M);  NaCl (0.05%; 25µS/cm; 1000µS/cm; 18mS/cm);

	Standard sea water;
	User defined
Compliance Certifications:	CE.WEEE
Conductivity Measurement at Stable Reading:	Yes
Conductivity measurement: Temperature correction:	None; Linear; NaCl Non-Linear Natural Water.
Conductivity Range:	0.01 µS/cm - 200.0 mS/cm
Conductivity resolution:	0.01 µS/cm - 0.1 mS/cm upon selected measuring range
Contents:	No
Custom Calibration Standards:	Yes
Data Export:	Download via USB connection to PC or flash memory device. Automatically transfer entire data log or as readings are taken.
Data Memory:	500 records/FIFO
Data storage:	Automatic, GLP ISO compliant reading data stored with calibration details.
Digital (intelligent) electrode inputs:	2 channels
Display:	Detailed mode/Large mode
Display Type:	240 x 160 pixel LCD with backlight illumination
DO Measurement Range:	0.1 - 20.0 mg/L (ppm) 1 - 200% saturation
DO Resolution:	0.1
DO sensor calibration:	* 100% (water-saturated air (100%) calibration)  * 100% with 0 (water-saturated air (100%) calibration with 0 point)  * mg/L (calibration with a specified dissolved oxygen concentration (mg/L) solution)  * mg/L with 0 (calibration with a specified dissolved oxygen concentration (mg/L) solution with 0 point)  * Factory (calibration with the default LDO calibration)
Electrode Type:	Intellical Standard Laboratory or Rugged Field
Environmental Conditions: Relative Humidity:	90 % relative humidity (non-condensing)
Environmental Conditions: Temperature:	0 - 60 °C (32 - 140 °F)
GLP Features:	Date; Time; Sample ID; Operator ID
Inputs:	2
Instrument:	Portable
IP Rating:	IP67
ISE Direct Measurement Range:	Yes
ISE Electrode Calibration:	2 - 5 points
Kit?:	Yes
Languages user interface:	English, French, German, Italian, Spanish, Danish, Dutch, Polish, Portuguese, Turkish, Swedish, Czech, Russian
Lock Function:	Continuous / Auto-stabilization ("press to read") / At Interval
Measurement method:	Probe specific programmed method settings
Model:	HQ40D – Multi/2 Channels
mV Measurement at Stable Reading:	Yes
mV Measurement Range:	-1500 - 1500 mV

mV Resolution:	0.1 mV
Needed Cable Length:	1
Operating Error Messages:	Clear text error messages displayed
Operating Interface:	Soft Touch Keypad
ORP Electrode Calibration:	Predefined ORP standards (including Zobell's solution)
Parameter:	pH/Oxydo Reduction Potential (ORP)
	Conductivity/Total Dissolved Solid (TDS)/Salinity/Resistivity
	Dissolved Oxygen (DO)
	Biochemical Oxygen Demand (BOD)
Parameters:	Ion Selective Electrode (ISE): Ammonia, Ammonium, Chloride, Fluoride, Nitrate, Sodium pH
	Conductivity
	NA
PC Data Transfer Software :	HQD Series Meter Data Transfer Utility
pH Buffer Sets:	Color-coded: 4.01, 7.00, 10.01 pH;  IUPAC: 1.679, 4.005, 7.000, 10.012, 12.45  DIN: 1.09, 4.65, 9.23  User-defined custom buffer sets
pH Electrode calibration:	1 - 3 Calibration points  Calibration summary data logged and displayed
pH Measurement Range:	0 - 14 pH
pH Resolution:	Selectable:  0.001/0.01/0.1 pH
Printer:	Yes, Optional
Probes included:	PHC20101, CDC40101
Salinity Measurement Range:	0 - 42 (ppt) (‰)
Salinity Resolution:	0.01 (ppt) (‰)
Sensor A:	PHC20101 (1 m)
Sensor B:	CDC40101 (1 m)
Sensor C:	NA
Sensors:	Sensor A: PHC20101, CDC40101  Sensor B: CDC40101  Sensor C:
Simultaneous measurements:	Yes, 2 channels
TDS Measurement Range:	0.00 mg/L - 50.0 g/L NaCl
TDS Resolution:	0.01 mg/L up - 0.1 g/L upon measuring range
Temperature Compensation:	Automatic Temperature compensation for pH
Temperature Measurement:	°C or °F
Temperature resolution:	0.1
Type of measurement:	QC Lab

Warranty:	36 months
Weight:	335 g (0.75 lb) without batteries; 430 g (0.95 lb) with
What's included?:	Meter package includes HQ40d Portable Meter, gel PHC201 pH probe with 1 m cable, CDC401 conductivity/TDS/salinity probe with 1 m cable, pH buffer solutions, pH storage solution, NaCl conductivity standard, probe stand, meter stand, 4 AA batteries, protective meter glove, power adapter, USB/DC power adapter for data transfer, quick-start guide, user manual, test certificate and documentation

---

## What's included?

Meter package includes HQ40d Portable Meter, gel PHC201 pH probe with 1 m cable, CDC401 conductivity/TDS/salinity probe with 1 m cable, pH buffer solutions, pH storage solution, NaCl conductivity standard, probe stand, meter stand, 4 AA batteries, protective meter glove, power adapter, USB/DC power adapter for data transfer, quick-start guide, user manual, test certificate and documentation