



Intellical ISECL181 Chloride (C|-) Ion Selective Electrode (ISE), 3 m cable

Product #: ISECL18103

ZAR Price: Contact Hach

Call for ship date

Intellical ISECL181 is a digital, combination, Chloride ion selective electrode (ISE) with a with a non-refillable gel Dritek reference with a double junction, ceramic porous pin and porous PTFE annular ring, and built-in temperature sensor. The electrode measures Chloride concentration in water samples. The laboratory version of this ISE is shockproff with its Epoxy plastic body. The Intellical ISECL181 probe is available with a 1 or 3 meter cable and is intended for laboratory use. The ISECL181's solid-state sensor design eliminates membrane replacement and allows for dry storage of the ISE. The ISECL181 is ideal for measuring chloride concentrations in wastewater, drinking water and general water quality applications.

Requires virtually no maintenance

The solid-state sensor design allows for DRY storage of the ISE without a shelf life. Also, the probe does not require the electrolyte to be refilled or membrane replacement.

Fast, stable, and accurate results

Intellical digital probes lock on the result when the measurement is stable, removing the guesswork in having a moving number. Additionally, the probe's large annular reference junction provides maximum surface area between sample and reference electrolyte for fast measurement stability.

Ultimate traceability in measurement history

Stored time and date stamp for each measurement, operator and sample ID, calibration history, parameter, and probe serial number

Can be moved between meters without the need to re-calibrate or re-enter measurement settings

Ideal for a multi-user environment with multiple HQD series Laboratory and Portable meters

Specifications

Accuracy: $\pm 0.02 \text{ mV} \text{ or } 0.05\%$, whichever is greater

Cable Length: 3 m

Electrode Type: Non-Refillable Dritek Gel Reference Element

ISA Required: Chloride ISA

(#2318069)

Junction: Double Junction (ceramic Porous Pin and annular porous PTFE)

Kit?: No

Length: 175 mm

Method Type: Field: Non-Refillable Dritek Gel Reference Element

Parameter: Chloride

Product Kit: Model: ISECL181

Accessories Included: None

Range: $0.1 \text{ mg/L } (3 \text{ x } 10^{-6} \text{ M}) - 35.5 \text{ g/L } (1 \text{ M}) \text{ C}|^{-1}$

Reference system: Ag/AgCl

Resolution: Selectable up to 4 significant digits

Sample Volume: 25 mL Sensor material: Epoxy

Sensor Type: Solid-state crystal membrane

Special Features: Dry storage & fast response time. No replacement membranes.

Temperature Accuracy: ± 0.3 °C

Temperature Range: 5 - 50 °C

Temperature resolution: 0.1 °C

Test requirements: Parameter Needed: Chloride

Minimum Sample Depth (mm): 26

Thermistor: ATC

Warranty: 6 months
Weight: 0.15 kg

What's included?: Intellical ISECL181 combination Chloride ISE, 3 m cable (ISECL18101), Test certificate, and

Basic User Manual.

What's included?

Intellical ISECL181 combination Chloride ISE, 3 m cable (ISECL18101), Test certificate, and Basic User Manual.

Required Accessories

Chloride Ionic Strength Adjustor (ISA) Powder Pillows, pk/100 (Item 2318069)