



Be Right™



Sension+ Conductivity electrode (general use)

Product #: LZW5060.97.0002
ZAR Price: Contact Hach
Available

Conductivity cell with Pt electrodes and Polycarbonate body.

Cell constant $C=1 \text{ cm}^{-1}$. Automatic temperature compensation. 1m cable. For portable meters.

Measuring range $0.2 \mu\text{S/cm} - 200 \text{ mS/cm}$, $0 - 80 \text{ }^\circ\text{C}$.

The electrode is suitable for general aqueous applications.

Ergonomic and robust

Specifications

Accuracy:	0.50% with EC5 Meter
Cable Length:	1 m
Connector:	Sension+ MP5
Dimensions (D x L) :	12 mm x 85 mm
Electrode Type:	Portable
Length:	85 mm
Material:	Sensor Body: Outside: Polycarbonate; Inside: Glass
Measuring range conductivity:	$0.2 \mu\text{S/cm} - 200 \text{ mS/cm}$
Parameter:	Conductivity
Range:	$0.2 \mu\text{S/cm} - 200 \text{ mS/cm}$
Sensor Type :	3-pole Platinum, $k = 1.0 \text{ cm}^{-1}$
Temperature Range:	$0 - 80 \text{ }^\circ\text{C}$
Thermistor :	Pt1000
Type:	Portable