



## Sension+ 5062 Robust conductivity electrode with Titanium body

**Product #:** LZW5062.97.0002  
**ZAR Price:** Contact Hach  
**Ships within 3-5 weeks**

Robust conductivity cell with Titanium electrodes and Titanium body for Sension+ portable meters. Cell constant  $k=1\text{ cm}^{-1}$ . Built-in Pt1000 for automatic temperature compensation. 1m cable, MP5 connector.

Measuring range  $5\text{ }\mu\text{S/cm}$  -  $50\text{ mS/cm}$ ,  $0 - 80\text{ }^{\circ}\text{C}$ . For taking measurements under extreme conditions, dirty and viscous products.

**Practically indestructible**

**Easy to clean**

**Built in Pt1000 for automatic temperature compensation.**

---

### Specifications

Accuracy:	0.50% with EC5 Meter
Cable Length:	1 m
Connector:	Sension+ MP5
Dimensions (D x L) :	12 mm x 85 mm
Electrode Type:	Portable
Length:	85 mm
Material:	Sensor Body: Titanium, Sensor Cell: Titanium
Measuring range conductivity:	$5\text{ }\mu\text{S/cm}$ - $50\text{ mS/cm}$
Parameter:	Conductivity
Sensor Type :	2-pole Titanium, $k = 0.3\text{ cm}^{-1}$
Special Features:	For harsh samples
Temperature Range:	$0 - 80\text{ }^{\circ}\text{C}$
Thermistor :	Pt1000
Type:	Portable
Warranty:	12 months