



## Sension+ pH combination stainless steel puncture electrode 5231 for Food Applications

**Product #:** LZW5231.97.0002

**ZAR Price:** Contact Hach

pH combination puncture electrode 5231 with one ceramic and one open diaphragm and solid electrolyte. Stainless steel body. Range 2-14 pH, 0-80 °C. S7 screw cap.

This electrode is suitable for semisolid food samples, e.g. cheeses, meats, fish, fruits, bread doughs, etc. The encapsulated reference ensures high stability and long lifetime.

### **Puncture electrode for semisolid food samples.**

316 stainless steel body, pH membrane with puncture design.

### **High stability and long lifetime**

Encapsulated Ag/AgCl reference system

---

## Specifications

Accuracy:	0.002 pH with MM374 Meter
Connector:	Screw cap S7
Electrode Type:	Laboratory
Electrolyte:	KCl + Glycerine
Filling Solution:	Non-refillable solid polymer
Material:	Sensor Body: 316 Stainless Steel
Operating temperature range:	0 - 80 °C
Parameter:	pH
Probe Junction :	1 ceramic, 1 open
Range:	2 - 14 pH
Sensor Type :	Glass
Special Features:	The encapsulated reference and the two diaphragms ensure high stability and long lifetime. The glycerine containing electrolyte ensures suitable flow rates for viscous samples.
Storage conditions:	Storage solution: LZW9512.99
Temperature Range:	0 - 80 °C
Warranty:	6 months