



## Sulfide TNTplus Vial Test (0.1-2.0 mg/L), 25 Tests

**Product #:**

**TNT861**

**ZAR Price:**

Contact Hach

No availability shown



**Hazardous**

Items with this mark may be considered hazardous under some shipping conditions.

If necessary, we will change your selected shipping method to accommodate these items.

### Expert Sulfide test made simple.

Sulfide TNTplus chemistry and your Hach spectrophotometer are engineered to simplify water analysis for accurate results, everytime. For photometric determination of Dissolved Sulfide by the Dimethyl-p-phenylenediamine method. With Sulfide TNTplus reagents, simply add sample and the included reagent to the vial, invert to mix, and insert into your Hach spectrophotometer! The Direct Read Technology will provide your Sulfide results to the exact mg/L! No more subjective visual determination necessary!

Upgrade from traditional visual test kit based methods to TNTplus Sulfide reagents today!

25 Water Sulfide vials per box.

#### Easy and safe handling

The innovative vial and reagent delivery makes tests easier to use than powder pillows or liquid reagents and significantly reduces spillage or contamination risk.

#### No reagent blank necessary

The high quality of TNTplus vials, tight reagent production controls, instrument calibration verification, and high instrument stability all combine to eliminate the need to run reagent blanks—saving you time and money!

#### Automatic method detection

The bar-coded vials allow for automatic method detection and measurement by the spectrophotometer, considerably increasing the speed of analysis. Errors are reduced as instrument averages 10 readings and rejects outliers from scratched, flawed, or dirty glassware.

#### Documented shelf life and COA

New 2D barcode details batch number and expiry date of reagents, which are documented along with the measurement result. An automatic warning is issued if expiry date has passed. Certificate of Analysis (COA) is available on RFID tag on the box.

---

### Specifications

According to standard:	ISO 10530-1991
EPA compliant:	Yes
Instrument:	DR3900, DR6000, DR1900, DR2800, DR3800, DR5000
Method:	10294
Number of tests:	25
Parameter:	Sulfide
Platform:	TNTplus

Range: 0.1 - 2.0 mg/L  $S^{2-}$

Storage conditions: 15 - 25 °C