



## Low Temperature BOD Incubator, LI6P (120V)

Product #: 2636200

 **Hazardous**

**OBSOLETE ITEM**  
This item is no longer available.

Items with this mark may be considered hazardous under some shipping conditions.

If necessary, we will change your selected shipping method to accommodate these items.

The Model LI6P BOD incubator is thermoelectric cooled, eliminating the need for a refrigeration compressor. The incubators include a mechanical convection system to ensure even air distribution, digital temperature set controller, over temperature limit control, and a temperature display. Two 75 pound capacity shelves are included. A one amp interior outlet allows the use of shakers, stirrers, roller bottles or BODTrak apparatus.

Low Temperature Incubators are ideal for testing sewage and wastewater as well as other low room temperature applications. 120V

Exterior dimensions: 30 x 31.5 x 33.5 in (76.2 x 80.01 x 85.09 cm)

### **Innovative peltier cooling technology**

Eliminates the need for a refrigeration compressor

### **Energy efficient**

The LI6P uses 78% less power than alternative models and reduce rppm air conditioning loads by 75%

### **Ideal for Biochemical Oxygen Demand**

Meets APHA specifications for BOD, 120 bottle capacity

### **Temperature set controller**

Includes an over-temperature limit control

### **Mechanical convection system**

Ensures even air distribution

---

## Specifications

Accuracy:	± 0.5 °C at 20 °C Temperature Uniformity
Capacity:	120 BOD Bottles
Electrical Specifications:	Volts: 100-120V
Manual Languages:	English
Method:	8043
Temperature Range:	15 - 40 °C
Weight:	111.1 kg Shipping Weight
	56.7 kg Net Weight
What's included?:	Two 75 pound capacity shelves

Adjustable leveling feet

---

## What's included?

Two 75 pound capacity shelvesAdjustable leveling feet