



SS7 with SC200, Standard 2 Channel

Product #: 2977200

OBSOLETE ITEM
This item is no longer available.

Measures high range turbidity levels.

The Surface Scatter 7 sc High Range Turbidimeter with SC200 controller offers superior performance features. It measures a turbidity range from 0 to 9999 NTU. Includes calibration cylinder, 4000 NTU Formazin, installation accessories, and instruction manual. Note: only one SS7 sc sensor can attach to one SC200 controller, if a second different sc sensor is required for this configuration please contact the Hach Company - Process Technical Group for further details.

Virtually maintenance-free, optics never touch the sample

The Hach Surface Scatter 7 sc Turbidimeter (SS7) is uniquely designed so that the light source and photocell never come in contact with the sample. In fluids with high loads of suspended solids this makes sample cell cleaning and replacement unnecessary.

Durable-manufactured with corrosion/heat-resistant materials for extended life

All wetted parts of the Hach Surface Scatter 7 sc turbidimeter are made with corrosion-resistant materials for extended life. The photo-detector and light source assemblies are protected from the effects of corrosive vapors and heated samples.

Wide turbidity measurement range

Use the Surface Scatter 7 sc to establish and maintain optimum process control for reliable monitoring. Applications for this version include drinking water effluent, wastewater effluent, flocculation and sedimentation, industrial process water, and food processing waste containing fat, starch, or oil.

Backed by a 2-year Warranty

Consistent with its long-standing reputation for quality and customer service, Hach Company warrants all Surface Scatter 7sc turbidimeters against defects in materials or workmanship for two years from the date of shipment.

Specifications

Accuracy:	±5% of reading or ±0.1 NTU (whichever is greater) from 0 - 2000 NTU
Accuracy 2:	± 10% of reading from 2000 - 9999 NTU
Alarm:	Relays can be programmed through sc controller for warning, alarm, feeder, event, pulse width modulation, and frequency control.
Ambient Temperature:	0 - 50 °C
Channels:	2 Channel
Controller:	Yes
Enclosure Construction:	Plastic instrument enclosure
Enclosure rating:	NEMA 12
Installation category:	Category II
Mounting:	Wall mount

Number of Channels:	2
Power requirements (Hz):	50/60 Hz
Power requirements (Voltage):	100 - 230 VAC
Range:	0 - 9999
Range 2:	Nephelometric Turbidity Units (NTU)
Relative Humidity:	5 - 95 % non-condensing
Repeatability:	1.0 % or ± 0.04 NTU, whichever is greater
Resolution:	0.1 NTU Between 1000 - 9999.9 NTU
Response time:	Initial response in 45 seconds
Sample Flow Rate:	Sample flow required 1.0 - 2.0 L/min (15 - 30 gal/hr)
Sample Input:	0.75 " NPT female thread
Sample Output:	1 " NPT female thread
Sample Temperature:	0 - 50 °C
Warranty:	24 months
Weight:	15.9 kg
What's included?:	Hach SC200 Controller, Mounting Hardware, SC200 Basic User Manual, SS7sc, Wall Mount Kit, Cylinder Brush, Light Source Alignment Template, 0.75 x 0.75 inch NPT Nipple, Calibration Cup, 0.75 inch NPT Ball Valve, SS7sc User Manual, and 500 mL 4000 NTU Formazin Standard. (The controller power cord is ordered separately.)

What's included?

Hach SC200 Controller, Mounting Hardware, SC200 Basic User Manual, SS7sc, Wall Mount Kit, Cylinder Brush, Light Source Alignment Template, 0.75 x 0.75 inch NPT Nipple, Calibration Cup, 0.75 inch NPT Ball Valve, SS7sc User Manual, and 500 mL 4000 NTU Formazin Standard. (The controller power cord is ordered separately.)

Required Accessories

- SC4500 Controller, Prognosys, 5x mA Output, 2 digital Sensors, 100-240 VAC, US plug (Item LXV525.99E11551)
- SC4500 Controller, Prognosys, 5x mA Output, 2 digital Sensors, 100-240 VAC, without power cord (Item LXV525.99A11551)
- SC4500 Controller, Prognosys, 5x mA Output, 1 digital Sensor, 100-240 VAC, without power cord (Item LXV525.99A11501)
- SC4500 Controller, Prognosys, 5x mA Output, 2 digital Sensors, 24 VDC, without plug (Item LXV525.99Z11551)