



## Orbisphere A1100 Oxygen (O<sub>2</sub>) EC sensor for Orbisphere 6110 Beverage Analyser

Product #: A1100-S00T

 **Hazardous**

**OBsolete ITEM**  
This item is no longer available.

Items with this mark may be considered hazardous under some shipping conditions.

Suggested replacements:

- GA2400-S00T

If necessary, we will change your selected shipping method to accomodate these items.

---

### Specifications

Accuracy:	±1% of reading, or ± lower measurement range, whichever is greater
Ambient Temperature:	-5 - 100 °C (23 - 212 °F) (due to electrolyte, but sensor will not be damaged up to 200°C / 392°F) (mechanical)
Certifications:	2004/108/EC - EN 61326-1
Flow Rate:	Recommended flow rate in flow chamber  2935A-A: 25 mL/min  2952A-A: 50 mL/min  2956A-A: 180 mL/min  29552A-A: 50 mL/min
Protection Class:	IP68
Range:	Range at 25 °C  2935A-A: 10 ppb - 400 ppm or 20 Pa - 1,000 kPa  2952A-A: 1 ppb - 80 ppm or 5 Pa - 200 kPa  2956A-A: 0.1 ppb - 20 ppm or 0.25 Pa - 50 kPa  29552A-A: 2 ppb - 80 ppm or 5 Pa - 200 kPa
Response Time:	2935A-A: 2.5 min  2952A-A: 38 s  2956A-A: 7.2 s  29552A-A: 90 s
Sample Pressure:	0 - 100
Temperature Range:	-5 - 60°C / 23 - 140 °F (without grille) (during

	measurement)
	-5 - 95°C / 23 - 203 °F (with a grille)
Warranty:	12 months
Weight:	0.3 kg
Wetted Materials:	Stainless Steel 1.4404 (AISI 316L), surface finish: N5, Ra < 0.4 µm
	Membrane (see specification table).
	No O-rings are in contact with the sample.
What's included?:	Sensor only.
	Controller, sensor cable, flow-chamber or process connection must be ordered separately.

## What's included?

Sensor only.Controller, sensor cable, flow-chamber or process connection must be ordered separately.