



Be Right™



## Soft Drink Oxygen Analyser

**Product #:** DGKM1100-TPO  
**ZAR Price:** Contact Hach  
**No availability shown**

**One solution for can corrosion and product stability control with mL of air and total package oxygen measurements.**

Kit consisting of controller, oxygen sensor, piercing device and accessories.

### **Quick and easy measurements in package for non-carbonated and carbonated drinks**

Using Hach's LDO technology, the Soft Drink Oxygen Analyser quickly measures dissolved oxygen in bottled and canned beverages in millilitres (mL). Easy to use, just place a (shaken) bottle or can on the platform and pierce. The analyser monitors the levels of oxygen and determines the air content in the headspace volume as well as the total air content in soft drinks on shaken packages.

### **Minimal impact to packing line due to fast measurement response**

Provides immediate oxygen readings with a measurement frequency of two seconds, reduces unnecessary line stoppages, and increases production uptime. Highly accurate readings for in-package air in non-carbonated and carbonated drinks.

### **Quantify oxygen levels for product stability**

Avoid product oxidation that can cause adverse changes in colour and product stability. The analyser calculates TPO using dissolved oxygen values on shaken packages with a repeatable TPO validation standard. Air calculator software is embedded to allow the data to be recorded, to accurately adjust and reduce CO<sub>2</sub> consumption.

### **Low maintenance with minimal downtime**

No drift for 12 months and no need to replace membranes or any electrolytes. The use of luminescent technology ensures the sensor doesn't require replacement of membranes or any electrolytes. Additionally, the sensors' accuracy is unaffected by process changes or pressure shocks.

---

## Specifications

Warranty:	12 months
What's included?:	KTO includes the M1100-S00H sensor + 410M/W1C00000 controller + 32510.03 3m cable

---

## What's included?

KTO includes the M1100-S00H sensor + 410M/W1C00000 controller + 32510.03 3m cable