



EZ3005 Chloride Analyser

Product #: EZ3005.XXXXXXXXXX
ZAR Price: Contact Hach

Online ion-selective Chloride measurements in industrial and environmental applications

ISE technology for optimal analytical performance

With limited maintenance requirements and reduced reagent consumption, the EZ3000 Series are the ideal choice for a wide range of water monitoring applications where ion-selective electrodes are the preferred analytical technique. Outstanding precision and stability is guaranteed by the temperaturecontrolled measurement.

Direct, discontinuous ISE method

Contrary to separate electrodes or other analysers in the market, the EZ3000 Series does not run a continuous measurement. The principle of discontinuous ISE analysis not only enhances control over conversion of ion activity to electric potential, it also eliminates risk of cross-contamination between cycles and reduces overall consumption of reagents.

The EZ3000 Series combine unique ISE technology with a set of analysis, control and communication features in an industrial analyser mainframe with designed for the highest performance:

- Automatic direct ion-selective measurements
- Smart automatic features
- Control and communication via industrial panel PC
- Standard 4 - 20 mA signal output with alarm processing
- Communication ports supporting connectivity to Modbus
- Multiple stream analysis
- Reduced reagent consumption

There are many additional options available. Please contact Hach for more details.

Specifications

| | |
|----------------------|---|
| Alarm: | 1x malfunctioning, 4x user-configurable, max. 24 VDC/0.5 A, potential free contacts |
| Ambient Temperature: | 10 - 30 °C ±4 °C deviation at 5 - 95% relative humidity (non-condensing) |
| Analogue Outputs: | Active 4 - 20 mA max. 500 Ohm load, standard 1, max. 8 (option) |

| | |
|---------------------------------|--|
| Automatic cleaning: | Yes |
| Calibration: | Automatic, 2-point; frequency freely programmable |
| Certifications: | CE compliant / UL certified |
| Cycle Time: | 5 minutes |
| Demineralised water: | For rinsing |
| Digital outputs: | Optional: Modbus (TCP/IP, RS485) |
| Dimensions (H x W x D): | 690 mm x 465 mm x 330 mm |
| Drain: | Atmospheric pressure, vented, min. Ø 32 mm |
| Earth connection: | Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ² |
| Instrument air: | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air |
| Interferences: | Bromide, sulphide, iodide, cyanide ions may interfere. Mercury must be absent. Ammonia and thiosulphate may interfere. Fats, oil, proteins, surfactants and tar. |
| Lower Limit of Detection (LOD): | 25 mg/L |
| Material: | Hinged part: Thermoform ABS, door: PMMA Wall section: Galvanised steel, powder coated |
| Measurement method: | Discontinuous, direct measurement by combined ion-selective electrode, conform with standard methods EPA 9212 and ASTM D512-12 |
| Measuring range: | 100 - 1,000 mg/L Cl ⁻ Optional: 25 - 250 mg/L Cl ⁻ 50 - 500 mg/L Cl ⁻ |
| Method: | Ionselective |
| Model: | EZ3005 |
| Number of sample streams: | 1, 2, 4 or 8 |
| Parameter: | Chloride |
| Power: | 100 - 240 VAC, 50/60 Hz Max. power consumption: 120 VA |
| Power supply: | 100 - 240 VAC, 50/60 Hz |
| Precision: | Better than 2% full scale range for standard test solutions |
| Protection Class: | Protection class: Analyser cabinet: IP44 / Panel PC: IP65 |
| Range: | 100 – 1000 mg/L |
| Reagent requirements: | Keep between 10 - 30 °C |
| Sample Flow Rate: | 100 - 300 mL/min |
| Sample Pressure: | By external overflow vessel |
| Sample Quality: | Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU |
| Sample Temperature: | 10 - 30 °C |
| Validation: | Automatic; frequency freely programmable |
| Warranty: | 12 months |
| Weight: | 25 kg |
| What's included?: | EZ3005 Chloride Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Electrode and Chloride Electrode, combined, and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution) |

What's included?

EZ3005 Chloride Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Electrode and Chloride Electrode, combined, and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)